Projectors

Pricelist
May 4th, 2009

X1130

Target User

- Home/Private Users
- Professional and Small Business Solutions
- Small and Medium Companies

Key Selling Points

- Sharp imagery
- Nature-friendly functionality
- Thorough usability

Standard Configuration

Display Technology	DLP™, Digital Light Display
Native Resolution	Native SVGA (800x600)
Compressed Resolution	Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)
Typical colors	16.7 million colors
Brightness (ANSI lumens)	2,300 ANSI Lumens (Standard), 1,840 ANSI Lumens (ECO)
Dimension (WxDxH)	264 x 225 x 95 mm (10.4"x 8.6"x 3.7")
Weight	5.07 lbs (2.3 Kg)
Contrast Ratio	2500:1
Noise Level	31 dBA (Standard mode), 26 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native, 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.56 ~ 2.8, f = 21.00mm ~ 23.00mm </br> 1:1.1 Manual Zoom and Manual Focus
Projection Screen	29"(73cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	53"@2m (1.86 ~ 2.04:1)
Projection Distance	3.9'(1.2m) ~ 37.2'(11.3m)
Horizontal Scan	31– 93kHz
Vertical Scan	48 ~ 86Hz
Lamp Type	189 W user replaceable UHP lamp
Lamp Life	4,000 Hours (ECO) - 3,000 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Audio	N/A
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	280 Watts (Operation), <5 Watts (Standby)
Uniformity	85%
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 </BR> Composite Video (RCA) x 1 </BR> S-Video (Mini DIN) x1 </BR> RS232 (Mini DIN) x 1 </BR>
Bundled Accessories	AC power cord </BR> VGA cable </BR> Composite video cable </BR> Remote control </BR> Battery for remote control </BR> Lens cap </BR> Carrying case </BR> User's guide (CD-ROM) </BR> Quick start guide </BR> Security card
Warranty	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.

Model	Part Number	Price	
X1130 Resolution 800x600, contrast ratio 2500:1, brightness 2.300 ANSI, noise level 31 dBA (std mode), 26 dBA (ECO mode), peso 2.3 kg, tecnologia ColorBoost II, +/-40 ºVertical keystone, Auto Keystone Correction, 53"@2m, da 1.2m a 11.3m, Blackboard mode, 4000h lamp life, tecnologia Acer Eco Projection, High Altitude Mode	EY.J9005.001	EUR 410.00	

X1230

Target User

- Home/Private Users
- Professional and Small Business Solutions
- Small and Medium Companies

Key Selling Points

- Sharp imagery
- Nature-friendly functionality
- Thorough usability

Standard Configuration

Display Technology	DLP™, Digital Light Display
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum SXGA+ (1,400 x 1,050), WXGA+ (1,440 x 900)
Typical colors	16.7 million colors
Brightness (ANSI lumens)	2,400 ANSI Lumens (Standard), 1,920 ANSI Lumens (ECO)
Dimension (WxDxH)	264 x 225 x 95 mm (10.4"x 8.6"x 3.7")
Weight	5.07 lbs (2.3 Kg)
Contrast Ratio	2500:1
Noise Level	31 dBA (Standard mode), 26 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native, 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.56 ~ 2.8, f = 21.00mm ~ 23.00mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen	29"(73cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	53"@2m (1.86 ~ 2.04:1)
Projection Distance	3.9'(1.2m) ~ 37.2'(11.3m)
Horizontal Scan	31– 93kHz
Vertical Scan	48 ~ 86Hz
Lamp Type	189 W user replaceable UHP lamp
Lamp Life	4,000 Hours (ECO) - 3,000 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Audio	One Internal Speaker with 2 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	280 Watts (Operation), <5 Watts (Standby)
Uniformity	85%
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 </br> Composite Video (RCA) x 1 </br> S-Video (Mini DIN) x1 </br> PC Audio (Stereo mini jack) x 1 </br> Analog RGB (D-sub) x 1 </br> PC Audio (Stereo mini jack) x 1 </br> RS232 (Mini DIN) x 1 </br>
Bundled Accessories	AC power cord </br> VGA cable </br> Composite video cable </br> Remote control </br> Battery for remote control </br> Lens cap </br> Carrying case </br> User's guide (CD-ROM) </br> Quick start guide </br> Security card </br>
Warranty	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.

Model	Part Number	Price	
X1230 Resolution 1024x768, contrast ratio 2500:1, brightness 2.400 ANSI, noise level 32 dBA (std mode), 28 dBA (ECO mode), wight 2.3 kg, ColorBoost II technology, +/-40°Vertical keystone, Auto Keystone Correction, 53"@2m, da 1.2m a 11.3m, Blackboard mode, Built in speaker, 4000h lamp life, Acer Eco Projection technology, High Altitude Mode	EY.J9105.001	EUR 536.00	

K10

Target User

- Home/Private Users
- Professional and Small Business Solutions
- Small and Medium Companies
- Enterprises

Key Selling Points

- Radiant display, light weight
- Convenient, mobile usability
- Enduring, efficient functionality

Standard Configuration

Display Technology	DLP™, Digital Light Processor with LED illumination
Native Resolution	Native SVGA (858 x 600)
Compressed Resolution	Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)
Typical Colors	16.7 Million Colors
Audio	No
Brightness (ANSI lumens)	100 ANSI Lumens
Contrast Ratio	2'000:1
Throw Ratio	50"@2m (1.97:1)
Noise Level	28 dBA
Weight	0.55 Kg (1.21 lbs)
Dimensions	127 x 122 x 48.5 mm
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
IR Remote Control	No
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Horizontal Scan Rate	31k – 69k Hz
Vertical Scan Rate	56 ~ 85 Hz
Projection mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Distance	2.0'(0.6m) ~ 7.9'(2.4m)
Projection Screen Size (Diagonal)	15"(38cm) ~ 60"(152cm)
Digital Zoom	No
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Lamp Life	LED life 20,000 Hours
Lamp Type	LED
Ceiling Mounting Capability	Not available
Power Consumption	55 Watts (Operation), </br> <1 Watts (Standby)
Power Supply	DC input 19V via a 90W power adapter (AC input 100~240V auto-switching to DC 19V)
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable Carrying case User's guide (CD-ROM) Quick start guide
Warranty	Acer projectors support a 2 year carry-in warranty and 90 days warranty for the lamp.

Model	Part Number	Price	
K10 Resolution 858x600, contrast ratio 2000:1, brightness 100 ANSI, noise level 28 dBA, peso 0.55 Kg, ultra-light and ultra-small, dimensions 127 x 122 x 48.5 mm, +/-40 ºVertical keystone, Auto Keystone Correction, 53"@2m, da 0.6m a 2.4m, LED lamp, 20.000h LED life, Low noise level, High Altitude Mode	EY.J8604.001	EUR 457.00	